

Configure, Don't Customize!

Event Mapping and Page and Field Configurator

Jim Marion, CPA.CITP
Principal Instructor
JSMPROS INC

ORACLE®

Gold
Partner

About your Presenter

- PeopleSoft Experience: 15 years
 - 5 years as a customer
 - 10 years with Oracle
- Conference presenter: 10 years
- Author: 3 books
 - PeopleTools
 - Lifecycle Management
 - PeopleSoft Mobile



jsmpros

VIRTUAL & ONSITE TRAINING




**PeopleTools
Training Led by
Industry Experts**

ORACLE

**Gold
Partner**

Logistics






Agenda

- Event Mapping
- Page and Field Configurator

Event Mapping

Review Existing Component

- Add **Travel Preferences XX** tile to homepage.
- Launch Component from tile
- We want to do the following:
 - Set Default Viewport (mobile)
 - Hide **Floor** field
 - Add icons next to Group Boxes
 - Change page title
 - Hide British Airways row



The screenshot shows a web browser window with the title "Travel Preferences". The URL is "hr92u025.example.com:8000/psc/ps/EMPLOYEE/HRMS/c/JSM_FLUID_MENU.JSM_TRAV_PREF_FL...". The page has a dark blue header with "Travel Preferences" and navigation icons. Below the header is a green "Travel Preferences" tile. The main content area is divided into three sections: "Air", "Hotel", and "Car".

Air Section: Includes dropdowns for "Seat" (Isle), "Position" (Front), "Bed" (King), "Floor" (High), "Size" (Full), and "Transmiss..." (Manual).

Table 1 (3 rows): Lists Airline Programs with columns for "Airline Program Name", "Airline Program ID", "Air Program Level", and "Loyalty Program Gift".

	Airline Program Name	Airline Program ID	Air Program Level	Loyalty Program Gift		
1	American Airlines	AA1234	Gold	Miles	+	-
2	British Airways	BR1234	Bronze	Miles	+	-
3	Qantas	QA1234	Platinum One	Miles	+	-

Table 2 (2 rows): Lists Hotel Programs with columns for "Hotel Program Name", "Hotel Program ID", "Hotel Program Level", and "Loyalty Program Gift".

	Hotel Program Name	Hotel Program ID	Hotel Program Level	Loyalty Program Gift		
1	Hyatt	ABC123	Discoverist	Points	+	-
2	Marriott	746935	Platinum	Points	+	-

Step 1: Create Application Class

```
import PT_RCF:ServiceInterface;

class ClassName implements PT_RCF:ServiceInterface
  method execute();
end-class;

method execute
  /* Extends/implements PT_RCF:ServiceInterface.execute */
  /* Code goes here */
end-method;
```

Step 2: Define a Service

- PeopleTools > Portal > Related Content Service > Define Related Content Service
- Create an App-class based service

Step 3: Map Service to Component

- PeopleTools > Portal > Related Content Service > Manage Related Content Service
- Select the target navigation item (Content Reference)
- Map the service to an event

Migration

- Insert the following into a project:
 - Application Class
 - Related Content Definition
 - Related Content Service using the portal `_PTCS_PTEVMAP`

Page and Field Configurator

Review Existing Component

- Add **Travel Prefs Search XX** tile to homepage.
- Launch Component from tile
- We want to do the following:
 - Hide Seat field
 - Set default value for Airline gift to Miles
 - Disable Position field data entry
 - Hide Transmission field if EMPLID is KU0007

The screenshot shows a web browser window titled "Travel Preferences" with a URL starting with "hr92u025.example.com". The page has a dark blue header with navigation icons. Below the header, there are three main sections: "Air", "Hotel", and "Car".

Air Section: Contains dropdown menus for "Seat" (set to "Isle"), "Position" (set to "Front"), "Bed" (set to "King"), "Floor" (set to "High"), "Size" (set to "Full"), and "Transmiss..." (set to "Manual").

Airline Program Table (3 rows):

	Airline Program Name	Airline Program ID	Air Program Level	Loyalty Program Gift		
1	American Airlines	AA1234	Gold	Miles	+	-
2	British Airways	BR1234	Bronze	Miles	+	-
3	Qantas	QA1234	Platinum One	Miles	+	-

Hotel Program Table (2 rows):

	Hotel Program Name	Hotel Program ID	Hotel Program Level	Loyalty Program Gift		
1	Hyatt	ABC123	Discoverist	Points	+	-
2	Marriott	746935	Platinum	Points	+	-

Configuration Steps

1. Navigate to Enterprise Components > Page and Field Configuration > Page and Field Configurator
2. Add a new value for the target component
3. Apply configuration changes
4. Use sequence number to target specific roles

Migration

- Data Migration Workbench dataset EOCC_CONFIGURATION

Q&A
